



BITUMEN PRESSURE DISTRIBUTOR

Technical Specification

Tank Capacity	TBPD 3 Ton	TBPD 4 TON	TBPD 6 TON
Length - L	2000 mm	2400 mm	3000 mm
Width - W	1800 mm	1800 mm	1860 mm
Height - H	1500 mm	1500 mm	1810 mm
Capacity	3000 liters	4000 liters	6000 liters
Manhole	600 mm	600 mm	600 mm - 1 nos.
Insulation	50 mm	50 mm	50 mm
Shape	Oval Shape	Rectangular oval Shape	Rectangular oval Shape
Burner	Compressed air type	Compressed air type	Compressed air type
Burner Fuel Tank	60 liters	60 liters	60 liters
Engine Fuel Tank	30 liters	30 liters	30 liters
Recommended Chassis	3760 mm - Wheel - base	3760 mm - Wheel - base	4470 mm - Wheel - base
Clear Chassis Length - CL	4550 mm	4850 mm	5450 mm

Standard Features

- Designed to suit standard truck chassis.
- Suitable for Bitumen / Emulsion Spraying.
- Insulated tank with high efficiency heating system.
- Spraying width ranging from 2.4 to 4.2 m.
- Digital Indicator Box for temperature & speed.
- Unique pressure cleaning system.
- Air-cooled diesel engine.
- Positive displacement gear pump.
- Hands spray system.
- Totally factory tested arrives ready to launch